



NOTE: ALL STATION AND OFFSETS ARE TAKEN FROM THE CENTERLINE OF CONSTRUCTION UNLESS OTHERWISE NOTED  
ALL DIMENSIONS ARE TO THE EDGE OF PAVEMENT UNLESS OTHERWISE NOTED

SLOPES AS FOLLOWS:  
 △ SLOPE 6% OR RATE OF S.E. WHICHEVER IS GREATER  
 □ S.E. RATE OF 2%, USE 6%  
 S.E. RATE OF 3%, USE 5%  
 S.E. RATE OF 4%, USE 4%  
 S.E. RATE OF 5%, USE 3%  
 S.E. RATE OF 6%, USE 2%

ALGEBRAIC DIFFERENCE IN SLOPES NOT TO EXCEED 8%.

- REQUIRED PAVEMENT**
- Ⓐ 165 LB/SQ YD - 1.5" ASPH. CONC. 12.5mm SUPERPAVE
  - Ⓑ 220 LB/SQ YD - 2" ASPH. CONC. 19 mm SUPERPAVE
  - Ⓒ 330 LB/SQ YD - 3" ASPH. CONC. 25 mm SUPERPAVE
  - Ⓓ 660 LB/SQ YD - 6" ASPH. CONC. 25 mm SUPERPAVE
  - Ⓔ 12" GRADED AGGREGATE BASE
  - Ⓕ ASPHALT LEVELING AS REQUIRED
  - Ⓖ 8 IN X 30 IN CONC. CURB & GUTTER TP. 2
  - Ⓗ 8 IN X 30 IN CONC. CURB & GUTTER TP. 7
  - Ⓙ CONCRETE INTEGRAL MEDIAN, 7.5"
  - Ⓚ 6" CONCRETE HEADER CURB, TYPE 7
  - Ⓛ 4" CONCRETE HEADER CURB, TYPE 9

**AECOM**  
 400 NORTHPARK TOWN CENTER  
 1000 ABERNATHY ROAD, N.E., SUITE 900  
 ATLANTA, GEORGIA 30328  
 TEL: (678) 808-8800 FAX: (678) 808-8400

REVISION DATES	
11/22/2016	

HENRY COUNTY SPLOST MANAGEMENT  
 SR 138 AND HEMPHILL ROAD  
 INTERSECTION IMPROVEMENT

**TYPICAL SECTIONS**

SR 138 AND HEMPHILL ROAD

DRAWING No.  
**05-002**